

FORMAX®

Div. of BESCORP, Inc.

FD 676

CONTINUOUS FORM
INDUSTRIAL BURSTERS

Standard Features

- **FD 676:** High Volume with poly rollers, slitters, tractor feed, and base
- **FD 680:** High Volume with imprinter, steel upper rollers, slitters, tractor feed and base
- **FD 689:** High Volume with merger, imprinter, steel upper rollers, slitters, tractor feed and base

Options:

- Center slitter
- Static eliminator
- Cylinders for 2-up printing
- Merger for 2-up forms
- Tri-color ink roll
- Power drop stacker
- Photo-cell counter (6-digit)
- Crash imprinting
- Last form shut-off switch

PAPER WEIGHT: Up to 140 lb. card stock,
up to 8 parts

Formax a Division of Bescorp, Inc.
New Hampshire, USA
Web Site: www.formax.com

LOCAL DEALER:

E.G. Brennan & Co., LLC

16116 Runnymede Street
Van Nuys, Ca. 91406

Phone: (818) 997-8061 Fax (818) 786-9165



FD 680

Three levels of performance are available to process continuous form documents. The Low-Volume Series processes at speeds of 0 to 200 feet per minute. The Medium-Volume Series processes at speeds of 15 to 350 feet per minute and is capable of handling forms up to 17" long. The High-Volume Series operates at speeds up to 500 feet per minute. All three Series offer a wide array of options to meet individual customer needs. The Low and Medium-Volume Series can be used up to five hours per day, five days a week. The High-Volume Series is capable of continuous operation, seven days a week.

Specifications:

Speed:	Variable, 30 - 500 feet per minute
Form Size:	2 3/4" - 19 1/4" (slitting) width 2 3/4" - 17" (non-slitting) width 2 3/4" - 17" length
Power:	115 volts AC 50/60 Hz
Weight:	FD 676 & FD 680 - 428 lbs.
Dimensions:	58" L x 41" W x 56" H (with base)
Safety Certifications:	UL

MEDIUM-VOLUME SERIES

Standard Features:

- **FD 566:** Tractor feed, slitters, base
- **FD 666:** Tractor feed, slitters, base (17" maximum form length)
- **FD 668:** FD 666 with an imprinter

Options:

- Imprinter, Imprint modules
- Center slitter
- Tri-color ink roller
- Cylinder for 2-up printing
- Merger for 2-up forms
- Extra-wide margin trimmers
- Photo-cell counter (6-digit)
- Last form shut-off switch (666 & 668)
- Power drop stacker
- Static eliminator

PAPER WEIGHT: 100 lb. total, up to 4 parts
(none exceeding 60 lb. tag stock)



FD 668

Specifications:

Speed:	Variable, 15 - 350 feet per minute
Form Size:	2 3/8" - 16" width 2 3/4" - 12" length, up to 17" (FD 666 & 668)
Power:	115 volts AC 50/60 Hz
Weight:	193 lbs. (FD 566) 352 lbs. (FD 666 & 668)
Dimensions:	58" L x 41" W x 56" H (with base)
Safety Certifications:	UL

LOW-VOLUME SERIES

Standard Features:

- **FD 546:** Variable speed, friction feed, slitters
- **FD 548:** FD 546 with base
- **FD 550:** Tractor feed, slitters and base
- **FD 552:** FD 550 with imprinter

Options:

- Center slitter
- Cylinders for 2-up printing
- Merger for 2-up forms
- Tri-color ink roll
- Power drop stacker
- Photo-cell counter (6-digit)
- Static eliminator

PAPER WEIGHT: 100 lb. total, up to 4 parts
(none exceeding 60 lb. tag stock)



FD 550

Specifications:

Speed:	Variable, 0 - 200 feet per minute
Form Size:	2 3/8" - 16" width 2 3/4" - 12" length
Power:	115 volts AC 50/60 Hz
Weight:	105 lbs. (FD 544) 88 lbs. (base)
Dimensions:	59" L x 32" W x 56.5" H (with base)
Safety Certifications:	UL